

# MARILYN MONOPRINT

by Andy Warhol® x Flavor Paper



Andy Warhol created a series of Marilyn Monroe silkscreen paintings shortly after her suicide in August 1962. Each piece in the photo-silkscreened paintings and screen prints derive from a publicity photo of Monroe from the 1953 film Niagra, which Warhol helped make into the most widespread, recognizable image of the actress. Towards the end of his career, Warhol revisited his most popular works from the 1960s and printed them as negatives, known as the Reversal series. Flavor Paper emulates the Marilyn Monroe Reversal paintings through a unique printing technique called monoprinting in which ink is applied directly to the screen prior to printing Marilyn Reversal overtop. This creates oneof-a-kind impressions; a wall composed of these large-scale prints would be extremely varied, yet consistent with a unified Marilyn foreground. This Flavor is available in four bombshell colorways with customization offered.

©/®/TM The Andy Warhol Foundation for the Visual Arts, Inc.

#### SPECS

 ROLL SIZE
 27" W x 180" L

 PRINT SCALE
 Each Marilyn Measures 27" W - x - 31" H

 PATTERN REPEAT
 35" /88.9cm

 SIDE TO SIDE MATCH
 HALF DROP

 MADE TO ORDER IN USA





# MARILYN MONOPRINT

by Andy Warhol® x Flavor Paper



### BLACK

PRINTING METHOD: HANDSCREEN
 GROUND: TYPE I CHROME MYLAR
 BACKING: NONWOVEN FIBER

• WEIGHT: 0.78 oz/sqft

• FIRE RATING: CLASS A, AS PER ASTM E 84 (ADHERED)
• FLAME SPREAD/SMOKE DEVELOPED: 15/205

• ECO: PRINTED WITH WATER BASED INKS (LATEX OR ECO-SOLVENT)

• INSTALLATION: COMES UNTRIMMED | PRO INSTALL RECOMMENDED

## DIAMOND DUST HOT PINK

PRINTING METHOD: HANDSCREEN
 GROUND: TYPE I CHROME MYLAR
 BACKING: NONWOVEN FIBER

• WEIGHT: 0.78 oz/sqft

• FIRE RATING: CLASS A, AS PER ASTM E 84 (ADHERED)

• FLAME SPREAD/SMOKE DEVELOPED: 15/205

• ECO: PRINTED WITH WATER BASED INKS (LATEX OR ECO-SOLVENT)

• INSTALLATION: COMES UNTRIMMED | PRO INSTALL RECOMMENDED





### DIAMOND DUST GOLD

PRINTING METHOD: HANDSCREEN
 GROUND: TYPE I BRIGHT GOLD MYLAR

• BACKING: NONWOVEN FIBER • WEIGHT: 0.78 oz/sqft

• FIRE RATING: CLASS A, AS PER ASTM E 84 (ADHERED)

• FLAME SPREAD/SMOKE DEVELOPED: 15/205

• ECO: PRINTED WITH WATER BASED INKS (LATEX OR ECO-SOLVENT)

• INSTALLATION: COMES UNTRIMMED | PRO INSTALL RECOMMENDED

#### WHITE

• PRINTING METHOD: HANDSCREEN
• GROUND: TYPE I CHROME MYLAR
• BACKING: NONWOYEN FIBER

• WEIGHT: 0.78 oz/sqft

• FIRE RATING: CLASS A, AS PER ASTM E 84 (ADHERED)

• FLAME SPREAD/SMOKE DEVELOPED: 15/205

• ECO: PRINTED WITH WATER BASED INKS (LATEX OR ECO-SOLVENT)

• INSTALLATION: COMES UNTRIMMED | PRO INSTALL RECOMMENDED